3M[™] Scotchshield[™] Automotive Security Films



Stay Cool

3M[™] Scotchshield[™] Automotive Security Films provide protection from the sun's heat and ultraviolet rays providing a 'cool effect' in more ways than one.



Increase Privacy

3M[™] Scotchshield[™] Automotive Security Films provide increased privacy for you and your valuables by shading your windows from the sun and prying eyes.



Safety & Security

3M[™] Scotchshield[™] Automotive Security Films enhances personal and property protection by holding your window together if the glass is shattered.



Stay Connected

3M[™] Scotchshield[™] Automotive Security Films are non-metallized and will not interfere with mobile phone, GPS and satellite radio reception.



UV Protection

3M[™] Scotchshield[™] Automotive Security Films provide vehicle occupants with significant protection from the dangers of the sun's UV rays.



Reduces Glare

3M[™] Scotchshield[™] Automotive Security Films significantly reduce glare from blinding sunlight, allowing you to see better and concentrate more on driving.



Limited Lifetime Warranty

3M[™] Scotchshield[™] Automotive Security Films are backed by a limited lifetime warranty should your window film need replacing from bubbling, peeling or blistering. Cool, safe, and secure, **3M[™] Scotchshield[™] Automotive Security Films** help shield you and your valuables by rejecting heat from the sun, increasing privacy, and holding shattered glass together, increasing the amount of time and effort it takes a thief to enter your vehicle, providing a powerful deterrent to smash and grab theft.

SAS 5		4	1% TSER
Visible Light Transmitted	6%	UV Rejection	99%
Total Solar Energy Rejected (TSER)	41%	Glare Reduction	94%
Visible Light Reflection	5%	Thickness (Mils)	4
SAS 20 39% TSER			
Visible Light Transmitted	20%	UV Rejection	98%
Total Solar Energy Rejected (TSER)	39%	Glare Reduction	80%
Visible Light Reflection	5%	Thickness (Mils)	4
SAS 35 36% TSER			
Visible Light Transmitted	33%	UV Rejection	99%
Total Solar Energy Rejected (TSER)	36%	Glare Reduction	67%
Visible Light Reflection	6%	Thickness (Mils)	4
SAS 50 30% TSER			
Visible Light Transmitted	50%	UV Rejection	97%
Total Solar Energy Rejected (TSER)	30%	Glare Reduction	50%
Visible Light Reflection	6%	Thickness (Mils)	4
SAS Clear 19% TSER			
Visible Light Transmitted	89%	UV Rejection	96%
Total Solar Energy Rejected (TSER)	19%	Glare Reduction	NA
Visible Light Reflection	9%	Thickness (Mils)	4



The Skin Cancer Foundation recommends many 3M Window Film products as effective UV Protectants.



3M and Scotchshield are trademarks of 3M Company

Warranty, Limited Remedy, and Disclaimer:

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.**

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Automotive Window Films 3M Renewable Energy Division 3M Center, Building 235-2S-27 St. Paul, MN 55144-1000 3M.com/windowfilm

Please recycle. © 3M 2013. All rights reserved. 98-0150-0294-6